

DETAIL NOT TO SCALE

Field Notes:

Point #1 — East 1/16 Corner of the NE 1/4, Section 22, T33N, R10W Found 20d spike as recorded by LaVern F. Schroeder, LS #312, plat of survey dated 10/09/1995, with the top bent. Pulled and replaced with a 6" mag nail.

SE 30.25 feet to top center fire hydrant. (30.27' R) NE 47.10 feet to set nail and washer side power pole. ENE 31.82 feet to north angle iron gate post.

Point #2 — Northeast Corner, Section 22, T33N, R10W
Found ½" Rebar 4" below gravel road surface. LaVern F. Schroeder records a water shutoff and stone. Said rebar fits recorded distance to 1/16 corner to the south (Point #1).

NE 34.22 feet to set nail and washer side light pole. SE 48.85 feet to top center fire hydrant. SSE 92.72 feet to set nail and washer side power pole. SW 55.38 feet to near corner telephone pedestal. On occupation centerline 4th Street bearing south. On occupation centerline east—west David Street.

Point #3 — North 1/16 Corner of the NE 1/4, Section 22, T33N, R10W Found $\frac{1}{2}$ Rebar 3" below grass surface.

SSE 83.42 feet to set nail and washer side light pole. SW 61.25 feet to SE corner house foundation. WSW 51.10 feet to NE corner house foundation. North 55 feet to occupation east—west Railroad Street. On range fence bearing south west of ballfield lights.

Points #6, #7 & #8 - Temporary Computed Point.

Points #9, #10, #11, & #12 - Set 5/8" X 30" Rebar with stamped plastic cap.

Project #HR995
Scale
Field Book 08
File Name PPDLYNCH.DWG
Revision
Sheet 2 of 2

This plat was prepared at the request of Joe Vetick, NPPD, Columbus, Nebraska.

Rasmussen Land Surveying, LLC 85774 US Highway 281 O'Nell, Nebraeka 68783 Phone/Fax (402) 482-5851 LOT 2, BLOCK 2, BURKHOLDER'S ADDITION TO THE VILLAGE OF LYNCH, BOYD COUNTY, NEBRASKA.

DETAIL FIELD NOTES

809-283 2/2